



PROMECH
—W A T E R—

**BALL VALVES FOR GAS
PRODUCT CATALOGUE**

www.promechgroup.com

BALL VALVE / 1-PARTIAL MONOBLOCK

GBV-1P



Dimension Range	DN15 → DN300 (PN40)
	DN65 → DN300 (PN16)
Body	GS-C25 Cast Steel (EN GS 200)
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Flanged / Single-Piece
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN16 - PN40

Optional: Body can be made in AISI 304 / AISI 316 stainless steel

BALL VALVE / 2-PARTIAL

GBV-2P



Dimension Range	DN15 → DN300
Body	GGG-40 Ductile Iron (EN GJS 400-15)
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Flanged / 2-Partial
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN16

The sizes DN250-DN300 are reduced flow.

BALL VALVE / 3-PARTIAL

GBV-3P



Dimension Range	DN15 → DN300
Body	GGG-40 Ductile Iron (EN GJS 400-15)
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Flanged / 3-Partial
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN16 - PN25 - PN40

Production size range from DN200 – DN300 for PN25.

BALL VALVE / 3-PARTIAL

GBV-3P-S



Dimension Range	DN15 → DN300
	DN65 → DN300
Body	GS-C25 Cast Steel (EN GS 200)
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Flanged / 3-Partial
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN16 - PN40

BALL VALVE / 2-PARTIAL

GBV-FF-2P



Dimension Range	DN15 → DN25
Body	GS-C25 Cast Steel (EN GS 200)
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Threaded (FF) / 2-Partial
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN25 - PN40

DN50 (Body and Ball:Ductile Iron)

BALL VALVE / 3-PARTIAL

GBV-FF-3P



Dimension Range	DN15 → DN100
Body	GS-C25 Cast Steel (EN GS 200) / PN40
Dimension Range	DN15 → DN100
Body	GGG-40 Ductile Iron (EN GJS 400-15) / PN25-40
Ball	AISI420 Stainless Steel
Gasket	PTFE
Connection Type	Threaded (FF) / 3-Partial
Max. Operating Temperature	180 ° C
Max. Working Pressure	PN25 - PN40